

# Dual Line / Buffer Amplifier

L200

The ATI NANOAMP L200 Dual Line/Buffer Amplifier is an inexpensive high performance amplifier which is ideal as a gain block, attenuator, impedance converter or signal splitter. It can also be configured as a stereo-to-mono summing amplifier with the addition of an internal jumper.

The inputs provide a balanced 40k ohm bridging impedance for line levels up to +24dBm. Two screwdriver adjust, full range gain controls provide 28dB gain at full clockwise rotation, unity gain at twelve o'clock and a smooth audio taper to full off. XLR connectors are used for inputs and outputs.

- +24dBm low distortion outputs drive balanced or unbalanced 600 ohm lines
- The L200 uses rugged XLR type input and output connectors
- Quiet external UL approved 24VDC wall mount power modules comfortably drive several NANOAMPS
- Battery packs and DC-to-DC converters for portable use are also available
- Stack them or rack mount one, two or three in only 1RU



# Dual Line / Buffer Amplifier

## Technical Specifications

L200

<b>GAIN</b>	28dB maximum, 0dB at 12 o'clock pot position
<b>NOMINAL LEVELS</b>	+4dBu in, +4dBm out to 600 ohm balanced load
<b>PEAK LEVELS</b>	+24dBu in, +24dBm out to 600 ohm balanced load
<b>NOISE, 20kHz BANDWIDTH</b>	-90dBm maximum
<b>HARMONIC DISTORTION 20Hz to 20kHz</b>	.02% Max at Peak Level .005% max. at Nominal Level
<b>FREQUENCY RESPONSE</b>	±.25dB, 20 to 20,000Hz
<b>CROSSTALK</b>	70dB minimum at 10kHz
<b>INPUT IMPEDANCE</b>	Balanced, 40kohm bridging
<b>OUTPUT IMPEDANCE</b>	Balanced, 40 ohms maximum impedance
<b>DIMENSIONS</b>	1.5" (3.8cm) H x 5.5" (14cm) W x 5.75" (14.6cm) D
<b>NET WEIGHT</b>	1.5 lbs. (0.7kg)
<b>CONNECTORS</b>	XLR (balanced inputs and outputs)
<b>POWER</b>	24VDC @ .07A
<b>MODEL NUMBER</b>	L200, CE marked certified
<b>POWER SUPPLIES</b>	120VAC Model WA100-1 external power supply (included); 230VAC Model WA100-2 available as exchange (specify when ordering). Nanoamps can share a single supply using loop thru DC cable (P/N 20602-1). Do not exceed rated supply current.
WA100-1	Wall mount power supply (UL) , 24VDC @ .4 amp, 115 VAC/60 Hz (included)
WA100-2	Table top power supply, 24VDC @ .4 amp, 230 VAC/50-60 Hz with IEC 320 male 3 pin AC input connector (exchange for WA100-1, specify when ordering). User supplies matching AC line cord for local power system.
BBU100-1	Battery Pack unit houses four 9V alkaline batteries (batteries not included). 4 to 6 hour life.
DC100-1	DC to DC converter powers several units from 12VDC mobile and belt pack batteries
20602-1	DC power cable assembly for looping the DC power between NanoAmps
<b>WARRANTY</b>	Limited, One Year Warranty